


LE-Series LED-backlit Display 22" | 24"

Ergonomic Displays for Home and Diverse Business Environments



The LE-Series is crafted with comfort and efficiency in mind. Its ergonomically-designed stand allows multiple viewing options, while its low blue light filter and flicker-free backlight ensure a comfortable viewing experience. Multiple connectivity options—DisplayPort, HDMI, and VGA—enable a wealth of multimedia applications and flexibility of connections. Various preset picture modes and colour settings are provided for different screen applications both at the workplace and in the home.





Maximized Comfort and Efficiency


An ergonomically-designed stand makes it possible to configure your workstation and create a working environment the way you want it. For comfort, convenience, and efficiency, tilt, pivot, or swivel the display, adjust its height, or shift to either portrait or landscape mode.

Eye Comfort

Eye comfort figures high on the list of strengths that define the LE-Series. The flicker-free backlight and blue light filter of the LE-Series ensure a comfortable viewing experience by reducing eyestrain after long periods of use.



LOW BLUE LIGHT



Flexible Connectivity and Multimedia Options

Connectivity versatility brings immense flexibility. Given its HDMI, DisplayPort, and VGA input options, you can easily connect an LE-Series display to your current or older peripherals, like PCs, laptops, or media players and enjoy Full HD resolution video and audio content.

Features

- Full HD 1920 x 1080 resolution
- Height adjustable stand allows users to tilt, pivot and swivel
- Blue-light filter and Flicker-free display technology reduces eye discomfort
- Versatile connectivity: DisplayPort, HDMI, VGA
- VESA mount compatibility for flexible installation

Specifications

LE-22E

LE-24E

Panel

Panel Type	LED-Backlit TFT LCD (TN Technology)	LED-Backlit TFT LCD (TN Technology)
Panel Size	21.5"	23.5"
Max. Resolution	FHD 1920 x 1080	FHD 1920 x 1080
Pixel Pitch	0.248 mm	0.272 mm
Brightness	250 cd/m ²	250 cd/m ²
Contrast Ratio	20,000,000:1 (DCR)	20,000,000:1 (DCR)
Viewing Angle (H/V)	170°/160°	170°/160°
Display Colour	16.7M	16.7M
Response Time	3 ms	3 ms

Frequency

Frequency (H)	30 kHz-95 kHz	30 kHz-95 kHz
Frequency (V)	48 Hz-76 Hz	48 Hz-76 Hz

Signal Input

DisplayPort	x 1	x 1
HDMI	1.4 x 1	1.4 x 1
VGA	15-Pin D-Sub x 1	15-Pin D-Sub x 1

Audio

Audio In	Stereo Audio Jack (3.5 mm)	Stereo Audio Jack (3.5 mm)
Audio Out	Stereo Audio Jack (3.5 mm)	Stereo Audio Jack (3.5 mm)
Internal Speakers	2W x 2	2W x 2

Power

Power Supply	Internal	Internal
Power Requirements	AC 100-240V, 50/60 Hz	AC 100-240V, 50/60 Hz
On Mode	19W (On)	19W (On)
Stand-by Mode	< 0.5W	< 0.5W
Off Mode	< 0.5W	< 0.5W

Operating Conditions

Temperature	0°C-40°C (32°F-104°F)	0°C-40°C (32°F-104°F)
Humidity	10%-85% (non-condensing)	10%-85% (non-condensing)

Storage Conditions

Temperature	-25°C-55°C (-13°F-131°F)	-25°C-55°C (-13°F-131°F)
Humidity	10%-85% (non-condensing)	10%-85% (non-condensing)

Mounting

VESA FPM/PMI	Yes (100 x 100 mm)	Yes (100 x 100 mm)
--------------	--------------------	--------------------

Stand

Tilt	-5° to 23°	-5° to 23°
Pivot	-2.5° to 92.5°	-2.5° to 92.5°
Swivel	± 70°	± 70°
Height Adjustment	0-110 mm	0-110 mm

Security

Kensington Security Slot	Yes	Yes
--------------------------	-----	-----

Dimensions

Product with Base (W x H x D)	505.6 x 494.7 x 248.9 mm (19.9" x 19.5" x 9.8")	566.0 x 510.2 x 249.0 mm (22.3" x 20.1" x 9.8")
Product w/o Base (W x H x D)	505.6 x 313.1 x 51.0 mm (19.9" x 12.3" x 2.0")	566.0 x 343.2 x 50.3 mm (22.3" x 13.5" x 2.0")
Packaging (W x H x D)	590.0 x 415.0 x 282.0 mm (23.2" x 16.3" x 11.1")	655.0 x 445.0 x 297.0 mm (25.8" x 17.5" x 11.7")

Weight

Product w/o Base	2.9 kg (6.4 lb)	3.4 kg (7.5 lb)
Product with Base	5.4 kg (11.9 lb)	5.8 kg (12.8 lb)
Packaging	7.5 kg (16.5 lb)	8.3 kg (18.3 lb)

Regulation Approval

Certifications & Compliance	FCC, CE, CB, BSMI, WEEE, RoHS, REACH, EAC	FCC, CE, CB, BSMI, WEEE, RoHS, REACH, EAC
-----------------------------	---	---

Accessories

Supplied	Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card	Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card
----------	--	--

Optional Accessories

Ceiling Mount (Landscape only)	CMP-01+WMK-03	CMP-01+WMK-03
Wall Mount (Landscape only)	WMA-01, WMK-01, WMK-03, PMK-01	WMA-01, WMK-01, WMK-03, PMK-01
Desk Mount (Landscape only)	DMC-01, DMC-02D, DMS-01D, DMS-01Q, ES-02	DMC-01, DMC-02D, DMS-01D, DMS-01Q, ES-02

Global Headquarters

Taipei, Taiwan

EMEA Regional Headquarters

Capelle a/d IJssel, The Netherlands

North & South America Regional Headquarters

San Jose, CA, U.S.A.

Asia-Pacific Regional Headquarters

Taipei, Taiwan

Canada Sales Office

Vancouver, B.C., Canada

China Sales Office

Shanghai, China

Czech Republic Sales Office

Brno, Czech Republic

Denmark Sales Office

Støvring, Denmark

Germany Sales Office

Mechernich, Germany

Italy Sales Office

Livorno, Italy

Poland Sales Office

Warsaw, Poland

Spain Sales Office

Barcelona, Spain

Ukraine Sales Office

Lviv, Ukraine

displays.agneovo.com