

# X-Series

LED-backlit Display 15" | 17" | 19" | 22" | 24"

## Versatility Beyond Limitations



The X-Series durable displays are designed for reliable 24/7 operation in the demanding environments. With the selectable gamma curves and versatile connectivity, the enhanced X-Series provides an optimal visual experience with excellent colour, brightness, and contrast ratio. NeoV™ Optical Glass and metal casing shield it from scratches and other damages which make it ideal for public, retail, laboratory, and industrial applications.



X-22E / X-24E



X-15E / X-17E / X-19E





Others



AG Neovo X-Series

### Enhanced Gamma Selection

Selectable gamma curves visually optimise different kinds of images. The AG Neovo specialised image settings enhance colour, brightness, sharpness and contrast ratio, allowing the X-Series to improve the light, shadows and colour balance of videos.

### Versatility, Productivity and Compatibility

Visualize critical data and engage with multiple video sources and PC applications with versatile connectivity options, including DisplayPort and HDMI, and PiP/PbP to increase productivity and efficiency. Selectable aspect ratio and zoom functions provide compatibility with different video sources.



### High Reliability

Designed for 24/7 operation, these durable metal-housed displays protected with NeoV™ Optical Glass take advantage of superior components to ensure a long product lifetime.

### Features

- LED-backlit technology with 1920 x 1080 / 1280 x 1024 / 1024 x 768 resolutions
- VA panel technology ensures accurate colours and offers high contrast ratios with wide viewing angles (24", 22" & 15" only)
- Anti-Burn-in™ technology prevents image ghosting
- NeoV™ Optical Glass and metal housing for excellent cleanability and protection
- Crisp 20,000,000:1 dynamic contrast ratio
- PiP/PbP functions enable multi-source viewing simultaneously
- Image enhancer: Deinterlace / Noise Reduction
- Versatile connectivity: DisplayPort, HDMI, DVI, VGA
- Front-sided IP22 Compliant (IEC 60529 Standard) (17", 19", 22" and 24" only)
- EcoSmart Sensor automatically adjusts brightness level according to ambient lighting conditions
- Flicker-free display technology reduces eye discomfort
- Built-in speakers
- Selectable gamma curves optimise different kinds of images
- Lockable control keys to prevent tampering in public environments
- Designed and developed for continuous 24/7 operation
- Premium-grade panel for high reliability and long product lifetime
- Available also in white

Specifications	X-15E	X-17E	X-19E
<b>Panel</b>			
Panel Type	LED-Backlit TFT LCD (VA Technology)	LED-Backlit TFT LCD (TN Technology)	LED-Backlit TFT LCD (TN Technology)
Panel Size	15.0"	17.0"	19.0"
Max. Resolution	XGA 1024 x 768	SXGA 1280 x 1024	SXGA 1280 x 1024
Pixel Pitch	0.297 mm	0.264 mm	0.294 mm
Brightness	300 cd/m <sup>2</sup>	250 cd/m <sup>2</sup>	250 cd/m <sup>2</sup>
Contrast Ratio	20,000,000:1 (DCR)	20,000,000:1 (DCR)	20,000,000:1 (DCR)
Viewing Angle (H/V)	176°/176°	170°/160°	170°/160°
Display Colour	16.2M	16.7M	16.7M
Response Time	5 ms	3 ms	3 ms
Surface Treatment	Anti-Glare Treatment (Haze 25%), 3H Hard Coating	Anti-Glare Treatment, 3H Hard Coating	Anti-Glare Treatment (Haze25%), 3H Hard Coating
<b>Frequency</b>			
Frequency (H)	24 kHz-83 kHz	24 kHz-83 kHz	24 kHz-83 kHz
Frequency (V)	50 Hz-75 Hz	50 Hz-75 Hz	50 Hz-75 Hz
<b>Signal Input</b>			
DisplayPort	x 1	x 1	x 1
HDMI	1.4 x 1	1.4 x 1	1.4 x 1
DVI	24-Pin DVI-D	24-Pin DVI-D	24-Pin DVI-D
VGA	15-Pin D-Sub x 1	15-Pin D-Sub x 1	15-Pin D-Sub x 1
<b>Audio</b>			
Audio In	Stereo Audio Jack (3.5 mm)	Stereo Audio Jack (3.5 mm)	Stereo Audio Jack (3.5 mm)
Internal Speakers	2W x 2	2W x 2	2W x 2
<b>Power</b>			
Power Requirements	DC 12V, 1.49A	DC 12V, 1.58A	DC 12V, 1.72A
On Mode	10W (On)	13W (On)	14W (On)
Standby Mode	< 0.5W	< 0.5W	< 0.5W
Off Mode	< 0.3W	< 0.3W	< 0.3W
Power Supply	External	External	External
<b>Glass</b>			
Thickness	3.0 mm (0.12")	3.0 mm (0.12")	3.0 mm (0.12")
Reflection Rate	< 1%	< 1%	< 1%
Transmission Rate	> 97%	> 97%	> 97%
MOHS Hardness	6	6	6
Pencil Hardness	9H	9H	9H
IK Rating	IK07	IK07	IK07
<b>Operating Conditions</b>			
Temperature	0°C-40°C (32°F-104°F)	0°C-40°C (32°F-104°F)	0°C-40°C (32°F-104°F)
Humidity	10%-90% (non-condensing)	10%-90% (non-condensing)	10%-90% (non-condensing)
<b>Storage Conditions</b>			
Temperature	-20°C-60°C (-4°F-140°F)	-20°C-60°C (-4°F-140°F)	-20°C-60°C (-4°F-140°F)
Humidity	5%-95% (non-condensing)	5%-95% (non-condensing)	5%-95% (non-condensing)
<b>Mounting</b>			
VESA FPMPMI	Yes (100 x 100 mm & 75 x 75 mm)	Yes (100 x 100 mm & 75 x 75 mm)	Yes (100 x 100 mm & 75 x 75 mm)
<b>Stand</b>			
Tilt	0° to 20°	0° to 22°	0° to 22°
<b>Security</b>			
Kensington Security Slot	Yes	Yes	Yes
<b>Dimensions</b>			
Product with Base (W x H x D)	380.0 x 359.0 x 155.0 mm (15.0" x 14.1" x 6.1")	409.4 x 398.2 x 175.0 mm (16.1" x 15.7" x 6.9")	445.4 x 420.2 x 175.0 mm (17.5" x 16.5" x 6.9")
Product w/o Base (W x H x D)	380.0 x 315.0 x 53.5 mm (15.0" x 14.1" x 2.1")	409.4 x 361.9 x 64.5 mm (16.1" x 15.7" x 2.5")	445.4 x 383.9 x 64.5 mm (17.5" x 15.1" x 2.5")
Packaging (W x H x D)	470.0 x 460.0 x 199.0 mm (18.5" x 18.1" x 7.8")	506.0 x 506.0 x 225.0 mm (19.9" x 19.9" x 8.9")	552.0 x 526.0 x 225.0 mm (21.7" x 20.7" x 8.9")
<b>Weight</b>			
Product w/o Base	4.2 kg (9.3 lb)	5.2 kg (11.5 lb)	6.0 kg (13.2 lb)
Product with Base	4.6 kg (10.1 lb)	6.0 kg (13.2 lb)	6.8 kg (15.0 lb)
Packaging	5.8 kg (12.8 lb)	7.5 kg (16.5 lb)	9.3kg ( 20.5 lb)
<b>Regulation Approval</b>			
Certifications & Compliance	CE, LVD, RoHS, WEEE, REACH	CE,LVD, RoHS, WEEE, REACH	LVD, CE, RoHS, WEEE, REACH, FCC, UKCA
Power Adaptor Certifications	Delta /ADP-40DD-B: CE, cUL/UL, RCM, WEEE, KCC, BSMI	Delta /ADP-40DD-B: CE, cUL/UL, RCM, WEEE, KCC, BSMI	Delta /ADP-40DD-B: CE, cUL/UL, RCM, WEEE, KCC, BSMI
<b>Accessories</b>			
Supplied	Power Adaptor, Power Cord, VGA Cable, Audio Cable, Quick Start Guide	Power Adaptor, Power Cord, VGA Cable, Audio Cable, Quick Start Guide	Power Adaptor, Power Cord, VGA Cable, Audio Cable, Quick Start Guide
<b>Optional Accessories</b>			
Ceiling Mount (Landscape only)	CMP-01+WMK-03	CMP-01+WMK-03	CMP-01+WMK-03
Wall Mount (Landscape only)	WMA-01, WMK-01, WMK-03, PMK-01	WMA-01, WMK-01, WMK-03, PMK-01	WMA-01, WMK-01, WMK-03, PMK-01
Desk mount (Landscape only)	DMC-01, DMC-02D, DMS-01D, ES-02	DMC-01, DMC-02D, DMS-01D, ES-02	DMC-01, DMC-02D, DMS-01D, ES-02

**Specifications**

**X-22E**

**X-24E**

**Panel**

Panel Type	LED-Backlit TFT LCD (VA Technology)	LED-Backlit TFT LCD (VA Technology)
Panel Size	21.5"	23.8"
Max. Resolution	FHD 1920 x 1080	FHD 1920 x 1080
Pixel Pitch	0.248 mm	0.274 mm
Brightness	250 cd/m <sup>2</sup>	250 cd/m <sup>2</sup>
Contrast Ratio	20,000,000:1 (DCR)	20,000,000:1 (DCR)
Viewing Angle (H/V)	178°/178°	178°/178°
Display Colour	16.7M	16.7M
Response Time	5 ms	5 ms
Surface Treatment	High resolution adaptable Anti-Glare Treatment (Haze25%), 3H Hard Coating	Seriesant1-Glare Treatment (Haze 40%), 3H Hard Coating

**Frequency**

Frequency (H)	24 kHz-83 kHz	24 kHz-83 kHz
Frequency (V)	50 Hz-75 Hz	50 Hz-75 Hz

**Signal Input**

DisplayPort	x 1	x 1
HDMI	1.4 x 1	1.4 x 1
DVI	24-Pin DVI-D	24-Pin DVI-D
VGA	15-Pin D-Sub x 1	15-Pin D-Sub x 1

**Audio**

Audio In	Stereo Audio Jack (3.5 mm)	Stereo Audio Jack (3.5 mm)
Internal Speakers	2W x 2	2W x 2

**Power**

Power Requirements	DC 12V, 3.33A	DC 12V, 3.33A
On Mode	16W (On)	18W (On)
Standby Mode	< 0.3W	< 0.5W
Off Mode	< 0.2W	< 0.3W
Power Supply	External	External

**Glass**

Thickness	3.0 mm (0.12")	3.0 mm (0.12")
Reflection Rate	< 1%	< 1%
Transmission Rate	> 97%	> 97%
MOHS Hardness	6	6
Pencil Hardness	9H	9H
IK Rating	IK07	IK07

**Operating Conditions**

Temperature	0°C-40°C (32°F-104°F)	0°C-40°C (32°F-104°F)
Humidity	10%-90% (non-condensing)	10%-90% (non-condensing)

**Storage Conditions**

Temperature	-20°C-60°C (-4°F-140°F)	-20°C-60°C (-4°F-140°F)
Humidity	5%-95% (non-condensing)	5%-95% (non-condensing)

**Mounting**

VESA FPMPI	Yes (100 x 100 mm & 75 x 75 mm)	Yes (100 x 100 mm & 75 x 75 mm)
------------	---------------------------------	---------------------------------

**Stand**

Tilt	0° to 15°	0° to 18°
------	-----------	-----------

**Security**

Kensington Security Slot	Yes	Yes
--------------------------	-----	-----

**Dimensions**

Product with Base (W x H x D)	513.2 x 368.5 x 155.0 mm (20.2" x 14.5" x 6.1")	562.4 x 392.8 x 196.0 mm (22.1" x 15.4" x 7.7")
Product w/o Base (W x H x D)	513.2 x 324.3 x 56.2 mm (20.2" x 12.8" x 2.2")	562.4 x 352.6 x 56.2 mm (22.1" x 13.9" x 2.2")
Packaging (W x H x D)	614.0 x 477.0 x 204.0 mm (24.2" x 18.8" x 8.0")	672.0 x 517.0 x 249.0 mm (26.5" x 20.4" x 9.8")

**Weight**

Product w/o Base	6.2 kg (13.7 lb)	7.0 kg (15.4 lb)
Product with Base	6.7 kg (14.7 lb)	7.8 kg (17.2 lb)
Packaging	8.8 kg (19.4 lb)	10.9 kg (24.0 lb)

**Regulation Approval**

Certifications & Compliance	CE, LVD, RoHS, WEEE, REACH, UKCA	CE, LVD, WEEE, RoHS, REACH
Power Adaptor Certifications	Delta /ADP-40DD-B: CE, cUL/UL, RCM, WEEE, KCC, BSMI	Delta /ADP-40DD-B: CE, cUL/UL, RCM, WEEE, KCC, BSMI

**Accessories**

Supplied	Power Adaptor, Power Cord, VGA Cable, Audio Cable, Quick Start Guide	Power Adaptor, Power Cord, VGA Cable, Audio Cable, Quick Start Guide
----------	--	--

**Optional Accessories**

Handle	HDL-02	HDL-02
Ceiling Mount (Landscape only)	CMP-01+WMK-03	CMP-01+WMK-03
Wall Mount (Landscape only)	WMA-01, WMK-01, WMK-03, PMK-01	WMA-01, WMK-01, WMK-03, PMK-01
Desk mount (Landscape only)	DMC-01, DMC-02D, DMS-01D, ES-02	DMC-01, DMC-02D, DMS-01D, ES-02

All specifications are subject to change without prior notice.

Copyright © 2026 AG Neovo. All rights reserved. The name AG Neovo is a trademark of AIC. All other trademarks are the property of their respective owners.

P/C: X15EA0/X17E00/X19EA0/X22EC0/X24EB0 Version 9.0, 20260319



**Global Headquarters**

Taipei, Taiwan

**EMEA Regional Headquarters**

Capelle a/d IJssel, The Netherlands

**North & South America Regional Headquarters**

San Jose, CA, U.S.A.

**Asia-Pacific Regional Headquarters**

Taipei, Taiwan

**Canada Sales Office**

Vancouver, B.C., Canada

**China Sales Office**

Shanghai, China

**Czech Republic Sales Office**

Brno, Czech Republic

**Denmark Sales Office**

Støvring, Denmark

**Germany Sales Office**

Mechernich, Germany

**Italy Sales Office**

Livorno, Italy

**Poland Sales Office**

Warsaw, Poland

**Spain Sales Office**

Barcelona, Spain

**Ukraine Sales Office**

Lviv, Ukraine

[www.agneovo.com](http://www.agneovo.com)