

## IFP-7503 75-INCH 4K INTERACTIVE FLAT PANEL DISPLAY














## **FEATURES**


- 4K UHD 3840 x 2160 resolution
- IPS Panel technology offers high color accuracy and wide viewing angles
- Incorporates IR touch technology
- 20-point simultaneous multi-touch capability
- · Two styluses for simultaneous annotation with two colors
- Android OS 9.0 platform
- Windows 11 ready plug and play support for Windows 7/8/10/11
- User-friendly Meetboard Whiteboard App for collaborative meetings
- The Screen-sharing App for multi-display control and wireless mirroring
- View, edit & create office documents with WPS Office Suite App
- Files sharing via email, QR Code, Cloud Drives, Samba and FTP portals
- A USB Type-C port for digital signal, data and 65W power delivery
- Built-in speakers and audio mini-jack in/out connections
- Wall mounts and the Wi-Fi module are included for quick installation
- An optional FMC-06 mobile cart allows easy movement and accessory assembly

Meetboard IFP-Series interactive display offers a future-proof all-in-one collaborative hub for various settings, such as classrooms, meeting rooms and coworking spaces. Built on the Android OS platform, Meetboard is ideal for getting meetings and presentations going right away, without the need for additional devices or software. Present, brainstorming and taking notes cannot be more effortless on Meetboard, bringing a neat and organized space.

## TECHNICAL DRAWING









## **SPECIFICATIONS**

P	9	n	۵	

Panel Type LED-Backlit TFT LCD (IPS Technology) Panel Size Max. Resolution UHD 3840 x 2160 Pixel Pitch 0.430 mm 350 cd/m<sup>2</sup> Brightness Contrast Ratio 1200 : 1 Viewing Angle (H/V) 178°/178° 1.07B Display Colour Response Time 5 ms Haze 25%, 2H, Anti-glare treatment Surface Treatment

Frequency Frequency (H) 30 kHz-80 kHz Frequency (V) 50 Hz-76 Hz

Signal Input

HDMI 2.0 x 3 VGA 15-Pin D-Sub x 1

Signal Output HDMI 2.0 x 1

**External Control** 

RS232 In 9-Pin D-Sub LAN RJ45 x 2

**Embedded Player** 

OS Android 9.0 CPU Quad core A73 Memory 4G Storage 32G

Other Connectivity

USB 2.0 x 1 / 3.0 x 4 / Type-C (DP 1.4 / Data 3.0 / PD:65W) Audio

Audio In Stereo Audio Jack (3.5 mm) Audio Out Stereo Audio Jack (3.5 mm), S/PDIF Internal Speakers

Touch Screen

Technology Infrared Touch Frame Positional Accuracy ±1.0 mm

USB 2.0 x 2 (Type-B) Panel Interface

Windows 2000/XP/Vista/CE 6.0 macOS Single Touch Plug & Play

Multi-touch Plug & Play Windows 7/8/10/11 Android/Linux (kernel version 3.5+) Chrome OS (39 or above)

Multi-touch Support by Driver macOS (supported by UPDD driver)

Power

Power Requirements AC 100-240V, 50/60 Hz On Mode 230W

Standby Mode < 0.5W Off Mode ΩW Power Supply Internal Glass

Thickness 3.2 mm (0.13") Transmission Rate ≥ 88% Hardness ≥ 8H Gloss 75±5 GU

Operating Conditions

Temperature 0°C-40°C (32°F-104°F) Humidity 10%-90% (non-condensing)

Storage Conditions

-20°C-60°C (-4°F-140°F) Humidity 10%-90% (non-condensing)

Temperature

Mounting VESA FPMPMI Yes (800 x 400 mm)

Dimensions

Product with Bracket (W x H x D) 1709.4 x 1019.9 x 107.7 mm (67.3" x40.2" x4.2") Product w/o Bracket (W x H x D) 1709.4 x 1019.9 x 85.7 mm (67.3" x40.2" x3.4") 1863.0 x 1140.0 x 225.0 mm (73.4" x44.9" x8.9")

Packaging (W x H x D) Weight Product w/o Base 48.4 kg (106.7 lb) Product with Base 49.9 kg (110.0 lb) 66.8 kg (147.3 lb)

Regulation Approval

CE, LVD, WEEE, RoHS, REACH, UKCA, EAC, FCC, BSMI, ICES-003 (Issue 7) Certifications & Compliance

Accessories

Packaging

Power Cord, HDMI Cable, USB Cable, Remote Control, Batteries, Quick Start Guide, Touch Pen, Supplied Wall Mount, Wi-Fi / Bluetooth Module

Optional Accessories

Wall Mount (Landscape only) LMK-03

FMC-03+LMK-04, FMC-04+LMK-04, FMC-05B, FWL-01B, FMC-06 Floor Mount (Landscape only)















