

IFP-8603 86-INCH 4K INTERACTIVE FLAT PANEL DISPLAY
















FEATURES

- 4K UHD 3840 x 2160 resolution
- IPS Panel technology offers high color accuracy and wide viewing angles
- Incorporates IR touch technology
- · 20-point simultaneous multi-touch capability
- Two styluses for simultaneous annotation with two colors
- Android OS 9.0 platform
- Windows 11 ready plug and play support for Windows 7/8/10/11
- User-friendly Meetboard Whiteboard App for collaborative meetings
- The Screen-sharing App for multi-display control and wireless mirroring
- View, edit & create office documents with WPS Office Suite App
- Files sharing via email, QR Code, Cloud Drives, Samba and FTP portals
- A USB Type-C port for digital signal, data and 65W power delivery
- Built-in speakers and audio mini-jack in/out connections
- Wall mounts and the Wi-Fi module are included for quick installation
- An optional FMC-06 mobile cart allows easy movement and accessory assembly

Meetboard IFP-Series interactive display offers a future-proof all-in-one collaborative hub for various settings, such as classrooms, meeting rooms and coworking spaces. Built on the Android OS platform, Meetboard is ideal for getting meetings and presentations going right away, without the need for additional devices or software. Present, brainstorming and taking notes cannot be more effortless on Meetboard, bringing a neat and organized space.

TECHNICAL DRAWING





SPECIFICATIONS

F	a	n	el

Panel Type LED-Backlit TFT LCD (IPS Technology) Panel Size 85.6" Max. Resolution UHD 3840 x 2160 Pixel Pitch 0.494 mm Brightness 350 cd/m² Contrast Ratio 1200:1 Viewing Angle (H/V) 178°/178° Display Colour 1.07B Response Time 5 ms Surface Treatment Haze 28%, 2H, Anti-glare treatment

Frequency Frequency (H) 30 kHz-80 kHz Frequency (V) 50 Hz-76 Hz

Signal Input

HDMI 2.0 x 3 VGA 15-Pin D-Sub x 1

Signal Output HDMI

External Control RS232 In 9-Pin D-Sub

LAN RJ45 x 2

Embedded Player OS Android 9.0 CPU Quad core A73

Memory 4G Storage 32G Other Connectivity

2.0 x 1 / 3.0 x 4 / Type-C (DP 1.4 / Data 3.0 / PD:65W) USB

Audio Stereo Audio Jack (3.5 mm) Audio In Stereo Audio Jack (3.5 mm), S/PDIF Audio Out

Internal Speakers 16W x 2 Touch Screen

Infrared Touch Frame Technology

Positional Accuracy ±1.0 mm Panel Interface USB 2.0 x 2 (Type-B)

Single Touch Plug & Play Windows 2000/XP/Vista/CE 6.0 macOS

Windows 7/8/10/11 Android/Linux (kernel version 3.5+) Chrome OS (39 or above) Multi-touch Plug & Play

Multi-touch Support by Driver macOS (supported by UPDD driver) Power

Power Requirements AC 100-240V, 50/60 Hz

On Mode 315W Standby Mode < 0.5W Off Mode 0W Power Supply Internal

Glass Thickness 3.2 mm (0.13") Transmission Rate ≥ 88% ≥ 8H Hardness Gloss 75±5 GU

Operating Conditions

Temperature 0°C-40°C (32°F-104°F) Humidity 10%-90% (non-condensing)

Storage Conditions

-20°C-60°C (-4°F-140°F) Temperature Humidity 10%-90% (non-condensing)

Mounting VESA FPMPMI Yes (800 x 600 mm)

Dimensions

Product with Bracket (W x H x D) 1957.0 x 1159.7 x 107.6 mm (77.1" x45.7" x4.2") Product w/o Bracket (W x H x D) 1957.0 x 1159.7 x 85.7 mm (77.1" x45.7" x3.4") 2110.0 x 1283.0 x 225.0 mm (83.1" x50.5" x8.9") Packaging (W x H x D)

Weight

Product w/o Base 62.0 kg (136.7 lb) Product with Base 63.5 kg (140.0 lb) Packaging 82.0 kg (180.8 lb)

Regulation Approval

Certifications & Compliance CE, LVD, WEEE, RoHS, REACH, UKCA, EAC, FCC, BSMI, ICES-003 (Issue 7)

Accessories

Power Cord, HDMI Cable, USB Cable, Remote Control, Batteries, Quick Start Guide, Touch Pen, Supplied

Wall Mount, Wi-Fi / Bluetooth Module

Optional Accessories

Floor Mount (Landscape only) FMC-03+LMK-04, FMC-04+LMK-04, FMC-05B, FWL-01B, FMC-06















