

# SMQ-5501 4K SURVEILLANCE DISPLAY WITH BNC




## FEATURES

- 4K UHD 3840 x 2160 resolution
- Anti-Burn-in™ technology prevents image ghosting
- Image Enhancer: 3D Comb Filter / Deinterlace / Noise Reduction
- Versatile connectivity: HDMI, DVI, VGA, Composite (BNC)
- BNC passive loop-through output port
- RS232/LAN Control - provides compatibility with control systems
- Black-level adjustment for presenting more details in dark images
- Selectable gamma curves optimise different kinds of images
- CCTV picture mode for maximum image detail in low light footage
- Optional blue or black screen when no input signal is detected
- Lockable control keys to prevent tampering in public environments
- Commercial-grade panel for high reliability and long product lifetime
- 24/7 Operation with a rugged metal housing design

The SMQ-5501 is a durable 55-inch 4K surveillance display. The display technology is future-proof and compatible with both analogue and digital surveillance systems. It provides 24/7 nonstop operation in the control rooms. The display supports up to 8MP camera image quality and can present crisp video footage, especially when zooming in the images for further detail checking. This level of image quality promotes more efficient and accurate video surveillance analysis. The SMQ-5501 features AG Neovo patented Anti-Burn-in™ Technology, preventing LCD burn-in during a surveillance operation. The technology also includes Neovo Controller software for easy management of multiple displays in security environments.

## TECHNICAL DRAWING



## SPECIFICATIONS

### Panel

Panel Type	LED-Backlit TFT LCD (IPS Technology)
Panel Size	54.6"
Max. Resolution	UHD 3840 x 2160
Pixel Pitch	0.315 mm
Brightness	350 cd/m <sup>2</sup>
Contrast Ratio	1200:1
Viewing Angle (H/V)	178°/178°
Display Colour	1.07G
Response Time	5 ms
Surface Treatment	Anti-Glare Treatment (Haze 1%), 3H Hard Coating

### Frequency

Frequency (H)	15 kHz ~ 135 kHz
Frequency (V)	24 Hz ~ 86 Hz

### Signal Input

HDMI	2.0 x 1
DVI	24-Pin DVI-D
VGA	15-Pin D-Sub x 1
Composite (CVBS)	BNC x 1

### Signal Output

Composite (CVBS)	BNC x 1
------------------	---------

### External Control

RS232 In	9-Pin D-Sub
LAN	RJ45 x 1

### Other Connectivity

USB	2.0 x 1 (Service Port)
-----	------------------------

### Audio

Audio In	Stereo Audio Jack (3.5 mm)
Audio Out	Stereo Audio Jack (3.5 mm), S/PDIF
Internal Speakers	5 W x 2

### Power

Power Requirements	AC 100-240V, 50/60 Hz
On Mode	99W (On)
Standby Mode	<0.5W
Off Mode	<0.3W
Power Supply	Internal

### Operating Conditions

Temperature	0°C-40°C (32°F-104°F)
Humidity	20%-85% (non-condensing)

### Storage Conditions

Temperature	-10°C-60°C (-4°F-140°F)
Humidity	10%-95% (non-condensing)

### Mounting

VESA FPM/PMI	Yes (400 x 400 mm)
--------------	--------------------

### Dimensions

Product w/o Base (W x H x D)	1243.2 x 714.0 x 69.6 mm (48.9" x 28.1" x 2.7")
Packaging (W x H x D)	1364.0 x 824.0 x 154.0 mm (53.7" x 32.4" x 6.1")

### Weight

Product w/o Base	14.8 kg (32.6 lb)
Packaging	18.6 kg (41.0 lb)

### Regulation Approval

Certifications & Compliance	CE, LVD, WEEE, RoHS, REACH, UKCA
-----------------------------	----------------------------------

### Accessories

Supplied	Power Cord, HDMI Cable, Remote Control (Batteries not included), Quick Start Guide
----------	--

### Optional Accessories

Ceiling Mount	CMP-01 + LMK-01
Video Wall Mount	VWM-01, VWM-02
Wall Mount	LMA-01, LMK-01, LMK-03, LMA-02
Floor Mount (Landscape only)	FMC-06, FMC-07
Desk mount (Landscape only)	DTS-01
Wall Mount (Portrait only)	WMK-05

