

# QM-5502 55-INCH 4K DIGITAL SIGNAGE DISPLAY


## FEATURES



- 4K UHD 3840 x 2160 resolution
- 400 nits brightness for indoor public use
- IPS Panel technology offers high colour accuracy and wide viewing angles
- Anti-Burn-in™ technology prevents image ghosting
- Built-in USB media playback for simple signage content delivery
- Versatile connectivity: HDMI x 3, VGA
- Alink™ function for synchronised powering on/off via HDMI
- Extensive display control: RS232, LAN and Neovo Controller software
- Black-level adjustment for presenting more details in dark images
- Selectable gamma curves optimise different kinds of images
- Flexible display orientation: Landscape/Portrait
- Rigorous screening of the components for mission-critical 24/7 applications
- HeatControl Sensors automatically reduce the screen brightness when temperature rises

The new QM-Series 4K digital signage displays are designed for digital signage applications that require crisper and clearer image presentation. Featuring a premium IPS panel for 24/7 operation, 4K UHD resolution with a wide viewing angle, and easy-to-use media playback via a USB drive. The QM-Series 4K digital signage displays are ideally used for retail stores, corporate meeting areas, hotels and other public spaces.

## TECHNICAL DRAWING



## SPECIFICATIONS

### Panel

Panel Type	LED-Backlit TFT LCD (IPS Technology)
Panel Size	54.6"
Max. Resolution	UHD 3840 x 2160
Pixel Pitch	0.315 mm
Brightness	400 cd/m <sup>2</sup>
Contrast Ratio	5000:1 (DCR) 1200:1 (CR)
Viewing Angle (H/V)	178°/178°
Display Colour	1.07G
Response Time	5 ms
Surface Treatment	Anti-Glare Treatment (Haze 1%), 3H

### Frequency

Frequency (H)	15 kHz-136 kHz
Frequency (V)	23 Hz-76 Hz

### Signal Input

HDMI	2.0 x 3
VGA	15-Pin D-Sub x 1

### External Control

IR Out	3.5 mm Phone Jack
RS232 In	9-Pin D-Sub
LAN	RJ45 x 1

### Other Connectivity

USB	2.0 x 1 (Service Port / Media Playback)
-----	---

### Audio

Audio In	Stereo Audio Jack (3.5 mm)
Audio Out	Stereo Audio Jack (RCA)
Internal Speakers	10W x 2

### Power

Power Supply	Internal
Power Requirements	AC 100-240V, 50/60 Hz
On Mode	135W (On)
Standby Mode	< 0.5W
Off Mode	< 0.3W

### Operating Conditions

Temperature	0°C-40°C (32°F-104°F)
Humidity	20%-80% (non-condensing)

### Storage Conditions

Temperature	-20°C-60°C (-4°F-140°F)
Humidity	10%-90% (non-condensing)

### Mounting

VESA FPM/PMI	Yes (400 x 400 mm)
--------------	--------------------

### Security

Kensington Security Slot	Yes
--------------------------	-----

### Dimensions

Product w/o Base (W x H x D)	1241.8 x 712.6 x 63.6 mm (48.9" x 28.1" x 2.5")
Packaging (W x H x D)	1350.0 x 860.0 x 160.0 mm (53.1" x 33.8" x 6.3")

### Weight

Product w/o Base	17.2 kg (37.9 lb)
Packaging	21.4 kg (47.2 lb)

### Regulation Approval

Certifications & Compliance	FCC, CE, LVD, UKCA, WEEE, RoHS, REACH, ICES-003 Issue 7, BSMI
-----------------------------	---

### Accessories

Supplied	HDMI Cable, Power Cord, Quick Start Guide, Remote Control (Batteries not included)
----------	--

### Optional Accessories

Ceiling Mount (Landscape only)	CMP-01 + LMK-01
Desk mount (Landscape only)	DTS-01
Floor Mount (Landscape only)	FMC-06, FMC-07
Video Wall Mount	VWM-01, VWM-02
Wall Mount	LMA-01, LMA-02
Wall Mount (Landscape only)	LMK-01, LMK-03
Wall Mount (Portrait only)	WMK-05



All specifications are subject to change without prior notice.  
Copyright © 2026 AG Neovo. All rights reserved.  
The name AG Neovo is a trademark of AIC.  
All other trademarks are the property of their respective owners.  
P/C: QM552B Version 6.0, 20260323