



## SPECIFICATIONS

<b>Panel</b>	
Panel Type	LED-Backlit TFT LCD (IPS Technology)
Panel Size	31.5"
Max. Resolution	FHD 1920 x 1080
Pixel Pitch	0.364 mm
Brightness	450 cd/m <sup>2</sup>
Contrast Ratio	1000:1
Viewing Angle (H/V)	178°/178°
Display Colour	16.7M
Response Time	5 ms
<b>Frequency</b>	
Frequency (H)	31 kHz-92 kHz
Frequency (V)	48 Hz-76 Hz
<b>Signal Input</b>	
DisplayPort	1.2 x 1 (BV:NO; AP:YES)
HDMI	2.0 x 1
DVI	24-Pin DVI-D
VGA	15-Pin D-Sub x 1
Composite (CVBS)	BNC x 1
<b>Signal Output</b>	
Composite (CVBS)	BNC x 1
<b>External Control</b>	
RS232 In	9-Pin D-Sub
LAN	RJ45 x 1
<b>Other Connectivity</b>	
USB	2.0 x 1 (Service Port / Media Playback)
<b>Audio</b>	
Audio In	Stereo Audio Jack (3.5 mm)
Audio Out	Stereo Audio Jack (3.5 mm), S/PDIF
Internal Speakers	10W x 2
<b>Power</b>	
Power Supply	Internal
Power Requirements	AC 100-240V, 50/60 Hz
On Mode	50W (On)
Standby Mode	<0.5W
Off Mode	0W
<b>Glass</b>	
Surface Treatment	AG
Thickness	3.2 mm (0.13")
Gloss	75±10%
Haze	3%-8%
MOHS Hardness	6
Pencil Hardness	8H
IK Rating	IK10
<b>Durability and Protection</b>	
IP rating	Front-Sided IP22
IK rating	IK10 (Entire unit)
<b>Operating Conditions</b>	
Temperature	0°C-40°C (32°F-104°F)
Humidity	20%-80% (non-condensing)
<b>Storage Conditions</b>	
Temperature	-10°C-60°C (-4°F-140°F)
Humidity	10%-80% (non-condensing)
<b>Mounting</b>	
VESA FPM/PMI	Yes (100 x 100 mm)
<b>Dimensions</b>	
Product w/o Base (W x H x D)	758.4 x 454.2 x 84.5 mm (29.9" x 17.9" x 3.3")
Packaging (W x H x D)	840.0 x 535.0 x 150.0 mm (33.1" x 21.1" x 5.9")
<b>Weight</b>	
Product w/o Base	10.2 kg (22.49 lb)
Packaging	12.0 kg (26.46 lb)
<b>Regulation Approval</b>	
Certifications & Compliance	FCC, CE, LVD, WEEE, RoHS, REACH, BSMI
<b>Accessories</b>	
Supplied	HDMI Cable, Power Cord, Quick Start Guide, Remote Control (Batteries not included)
<b>Optional Accessories</b>	
Desk Mount	DTS-01
Ceiling Mount (Landscape only)	CMP-01 + LMK-02, CMP-01 + WMK-03
Wall Mount (Landscape only)	LMA-01, LMK-02, WMA-01, WMK-01, WMK-03



All specifications are subject to change without prior notice.  
Copyright © 2026 AG Neovo. All rights reserved.  
The name AG Neovo is a trademark of AIC.  
All other trademarks are the property of their respective owners.  
P/C: TN3210 Version 4.1(BV), 20260515