

DS3251 32-INCH ALL-IN-ONE FHD DIGITAL SIGNAGE DISPLAY


FEATURES



- FHD 1920 x 1080 resolution
- 500 nits brightness panel offers clear images even in well-lit environments.
- 8.8mm ultra-narrow bezel for a seamless and immersive viewing experience.
- Slim profile of 40mm fits closely to the wall, ensuring a sleek, integrated look.
- 25% haze anti-glare for a glare-free viewing experience in any lighting condition.
- Anti-Burn-in™ technology prevents image ghosting.
- Premium commercial-grade panel designed for 24/7 use.
- Flexible display orientation, with landscape and portrait options.
- Android 9.0 & 16GB Storage capacity for apps and media.
- USB media playback directly from USB storage devices quickly and easily.
- Built-in Wi-Fi 5 and Bluetooth options for easy integration into your existing network and connection to peripheral devices.
- Integrated web browser on accessing online content directly from your display.
- Wireless screen sharing without any apps downloaded.
- User-friendly content management system offers an intuitive interface for updating and scheduling content with ease.
- Embedded advanced content scheduling function for easy arrangement of content playback schedule.
- 3 x HDMI ports provide connections to an external media player and a variety of HD sources.
- RS232 & LAN control for incorporation into a managed network for centralized control.
- Compatible with Neovo Controller software across brands and consolidating command codes.

The DS3251, a 32-inch FHD all-in-one digital signage display boasting 500 nits brightness, is powered by the Android 9.0 operating system. It provides a one-stop solution for comprehensive content management, facilitating the creation, management, and publishing of eye-catching content. With advanced scheduling and seamless integration of cutting-edge features, it offers versatile connectivity, sleek design, and immersive visuals. This display is ideal for businesses that prioritize customer engagement with timely and visually striking information.

TECHNICAL DRAWING



SPECIFICATIONS

Panel

Panel Type	LED-Backlit TFT LCD (VA Technology)
Panel Size	31.5"
Max. Resolution	FHD 1920 x 1080
Pixel Pitch	0.364 mm
Brightness	500 cd/m ²
Contrast Ratio	4000:1
Viewing Angle (H/V)	178°/178°
Display Colour	16.7M
Response Time	5 ms
Surface Treatment	Haze 25% · Hard Coating (3H)

Frequency

Frequency (H)	18 kHz-68 kHz
Frequency (V)	24 Hz-60 Hz

Signal Input

HDMI	2.0 x 3
------	---------

External Control

RS232 In	9-Pin D-Sub
LAN	RJ45 x 1

Embedded Player

OS	Android 9.0
CPU	A35*4
Memory	2G
Storage	16G

Other Connectivity

USB	2.0 x 2 (Service Port / Media Playback)
-----	---

Audio

Audio Out	Stereo Audio Jack (3.5 mm)
Internal Speakers	10W x 2

Power

Power Supply	Internal
Power Requirements	AC 100-240V, 50/60 Hz
On Mode	40W (On)
On Mode (Max)	70W (Max)
Standby Mode	< 0.5W

Operating Conditions

Temperature	0°C-40°C (32°F-104°F)
Humidity	20%-80% (non-condensing)

Storage Conditions

Temperature	-20°C-60°C (-4°F-140°F)
Humidity	20%-80% (non-condensing)

Mounting

VESA FPMPI	150 mm x 200 mm
------------	-----------------

Dimensions

Bezel Width	Even bezel 8.8 mm
Product w/o Base (W x H x D)	724.6 x 419.8 x 40.0 mm (28.5" x 16.5" x 1.6")
Packaging (W x H x D)	795.0 x 520.0 x 115.0 mm (31.3" x 20.5" x 4.5")

Weight

Product w/o Base	5.4 kg (11.9 lb)
Packaging	7.0 kg (15.4 lb)

Regulation Approval

Certifications & Compliance	FCC, ICES-003 Issue 7, WEEE, RoHS, REACH
-----------------------------	--

Accessories

Supplied	HDMI Cable, Power Cord, Quick Start Guide, Remote Control (Batteries not included)
----------	--

Optional Accessories

Ceiling Mount (Landscape only)	CMP-01 + LMK-02
Wall Mount (Landscape only)	LMK-02
Desk mount (Landscape only)	DTS-01



All specifications are subject to change without prior notice.

Copyright © 2025 AG Neovo. All rights reserved.

The name AG Neovo is a trademark of AIC.

All other trademarks are the property of their respective owners.

P/C: DS3210 Version 1.0, 20251003