


FEATURES



- **Ultra-Slim Border Design:** Narrow bezels maximise screen area and deliver a clean, modern appearance for office use.
- **Enhanced Ergonomic Design:** Height, tilt, and swivel adjustments support comfortable viewing and proper posture.
- **Eye Comfort Technology:** Flicker-free and low blue light features help reduce eye fatigue during long work hours.
- **27" Full HD IPS Display:** Provides sharp visuals and consistent colour accuracy from wide viewing angles.
- **120Hz Refresh Rate:** Ensures smoother scrolling and on-screen movement for improved visual comfort.
- **Multiple Connectivity Options:** HDMI and Display ports inputs support easy connection to various devices.

The LH2704 desktop monitor is designed for a comfortable and productive workday. Easily adjust the screen's height and angle to suit users posture, while the Full HD IPS display keeps text and visuals clear and sharp. With simple plug and play HDMI and Display ports connections for laptop or PC, the LH2704 makes everyday office tasks smooth and efficient.

TECHNICAL DRAWING



SPECIFICATIONS

Panel

Panel Type	LED-Backlit TFT LCD (IPS Technology)
Panel Size	27.0"
Max. Resolution	FHD 1920 x 1080
Pixel Pitch	0.311 mm
Brightness	250 cd/m ²
Contrast Ratio	20,000,000:1 (DCR)
Viewing Angle (H/V)	178°/178°
Display Colour	16.7M
Response Time	5 ms
Surface Treatment	Anti-Glare Treatment (Haze 25%), 3H Hard Coating

Frequency

Frequency (H)	30 kHz-138 kHz
Frequency (V)	48 Hz-120 Hz

Signal Input

DisplayPort	x 1
HDMI	1.4 x 1

Audio

Earphone	Stereo Audio Jack (3.5 mm)
Internal Speakers	2 W x 2

Power

Power Supply	External
Power Requirements	DC 12V, 3.0A
On Mode	18W (On)
Standby Mode	< 0.5W
Off Mode	< 0.3W

Operating Conditions

Temperature	0°C-40°C (32°F-104°F)
Humidity	20%-85% (non-condensing)

Storage Conditions

Temperature	-20°C-60°C (-4°F-140°F)
Humidity	5%-90% (non-condensing)

Mounting

VESA FPM/PMI	Yes (100 x 100 mm)
--------------	--------------------

Stand

Tilt	-5° to 20°
Pivot	0° to 90°
Swivel	± 30°
Height Adjustment	0-100 mm

Security

Kensington Security Slot	Yes
--------------------------	-----

Dimensions

Bezel Width	3.6 mm (Top/Left/Right) 18.0 mm (Bottom)
Product with Base (W x H x D)	615.1 x 507.8 x 188.6 mm (24.2" x 20.0" x 7.4")
Product w/o Base (W x H x D)	615.1 x 364.1 x 46.3 mm (24.2" x 14.3" x 1.8")
Packaging (W x H x D)	820.0 x 480.0 x 168.0 mm (32.3" x 18.9" x 6.6")

Weight

Product with Base	4.9 kg (10.8 lb)
Product w/o Base	3.2 kg (7.1 lb)
Packaging	7.1 kg (15.7 lb)

Regulation Approval

Certifications & Compliance	CE, LVD, WEEE, RoHS, REACH, UKCA
Power Adaptor Certifications	CE, PSB, BSMI, KCC, CCC, RCM, ETL, FCC, ICES-003, WEEE, RoHS

Accessories

Supplied	HDMI Cable, Power Adapter, Quick Start Guide
----------	--

Optional Accessories

Ceiling Mount	CMP-01 + WMK-03
Wall Mount	WMA-01, WMK-01, WMK-03, PMK-01
Desk Mount	DMC-01
Stand	ES-02

*Wall mounting screws are purchased separately. Use 4x M/F hex standoffs, M4 x 0.7, SUS304, Hex 8 mm / Body 9 mm / Thread 6 mm.



All specifications are subject to change without prior notice.
Copyright © 2026 AG Neovo. All rights reserved.
The name AG Neovo is a trademark of AIC.
All other trademarks are the property of their respective owners.
P/C: LH2740 Version 1.0, 20260817